








A polyelectrolytic fuel cell and the method of controlling the operation thereof

Patent number: EP0716463
Publication date: 1996-06-12
Inventor: MIZUNO SEIJI (JP)
Applicant: TOYOTA MOTOR CO LTD (JP)
Classification:
 - international: H01M8/04; H01M8/24
 - european: H01M8/04C2, H01M8/04C2E2, H01M8/24D
Application number: EP19950117605 19951108
Priority number(s): JP19940302948 19941111; JP19940332072 19941212

Also published as:

 US5939218 (A1)
 EP0716463 (A3)


Cited documents:

 US3432356
 WO9318556
 EP0417464
 EP0596366
 EP0596367
 more >>

Abstract of EP0716463

When at least either one of the output voltage and internal resistance of a plurality of stacked unit cells (11a) and the humidity of oxidizing gas being discharged has deviated from the tolerance, the supply conditions of oxidizing gas to the polyelectrolytic fuel cell are changed. Specifically, when output voltage had decreased, when internal resistance has increased, or when the humidity of discharge gas has increased, the flow rate of oxidizing gas is increased, or its pressure increases, or the humidity of oxidizing gas is reduced. As a result, moisture inside the cell is removed and flooding and the resulting falls in output voltage are prevented. In addition, the generation of hydrogen gas in the passages for oxidizing gas is contained.

FIG. 1



Data supplied from the esp@cenet database - Worldwide